


D-Link DEM-310GT 1000BASE-LX Single-Mode 10 Km LC SFP Transceiver

Product Specification

| | |
|---|---|
| Brand | D-Link |
| Model | DEM-310GT |
| Type | SFP Transceiver |
| Standards | 100-SM-LC-L Fiber Channel FC-PI |
| Supported | Single-Mode Fiber Media |
| Distance | 10 KM |
| Speed | 1 Gbps |
| Compliant Standards | IEEE-802.3z 1000BASE-LX |
| Connector type | Duplex LC Connector |
| EMI | FCC Class B \| ICES-003 Class B \| CE Class B \| VCCI Class B |
| Safety | FDA/CDRH \| TUV \| cUL |
| Wave length | 1310 nm |
| Interface | MIN.: - 21 dBm |
| Sensitivity | -21 dBm |
| Cable Type | Single-mode 9/125um fiber \| Reach 10km - multi-mode 50/125um fiber \| reach 2km - multi-mode 62.5/125um fiber \| Reach 550m |
| Heat Generated | 1.78kJ/h |

| | |
|---|---|
| Additional Features | Hot Pluggable \| RoHS Compliant \| MSA Compliant \| F1 Hardware version |
| Power | 3.3V |
| Max Input Power | 300mA |
| Operation Temperature | 0-70°C |
| Storage Temperature | -40-85°C |
| Supported Humidity | 10% ~ 90% |
| Weight | 16.5 Gram |
| Dimensions | 13.4mm x 56.4mm x 10.35 MM (W*D*H) |