

## HP ScanJet Pro 2000 s1 Sheet-feed Scanner | L2759A

## Product Specification

Brand	HP
Series	ScanJet Pro
Model	Pro 2000 s1-L2759A
Scanner Type	Sheetfed
Scan Resolution	Optical Up to 600 dpi (color and mono, Sheet-feed)
Output Resolution Dpi Settings	75; 150; 200; 240; 300; 400; 500; 600; 1200 ppi
Duty Cycle	Recommended for 2000 pages per day
Bit Depth	24-bits external 48-bits internal
Auto document feeder	50 sheets of 75 g/m² paper
Scan size (ADF)	Maximum 216 x 863 mm   Minimum 50.8 x 50.8 mm
Scan file format	For text & images: PDF, JPEG, PNG, BMP, TIFF, Text (.txt), Rich Text (rtf) and Searchable PDF

Media weights supported, ADF	50 to 180 g/m2
Media size (ADF)	U.SLetter: $215.9 \times 279.4 \text{ mm}$ (8.5 x 11 in); U.SLegal: $215.9 \times 355.6 \text{ mm}$ (8.5 x 14 in); U.SExecutive: $184.2 \times 266.7 \text{ mm}$ (7.25 x 10.5 in); ISO A4: $210 \times 297 \text{ mm}$ (8.3 x 11.7 in); JIS B5: $182 \times 257 \text{ mm}$ (7.2 x 10.1 in); ISO B5: $176 \times 250 \text{ mm}$ (7.0 x 9.9 in); ISO A5: $148 \times 210 \text{ mm}$ (5.8 x 8.3 in); ISO A6: $105 \times 148 \text{ mm}$ (5.8 x 4.1 in); ISO A7: $74 \times 104 \text{ mm}$ (2.9 x 4.1 in); ISO A8: $52 \times 74 \text{ mm}$ (2.0 x 2.9 in)
Media type	Cut Sheet Paper, Printed Paper (Laser and ink), Pre-Punched Paper, Bank Checks, Business Cards, Freight Bills, Carbonless forms, Previously stapled media with staple removed
Scan technology	CMOS CIS
Levels of grayscale	256
Color scanning	Yes
Scan speed	Automatic document feeder Up to 30 ppm/60 ipm
Scan Speed	OCR (A4) < 10 sec
Task speed	10 x 15 cm (4 x 6 in) color photo to file (200 dpi, 24-bit, tiff): about 6.90 sec for single image scan; OCR A4 (8.27 x 11.69 in), 300 dpi, 24-bit to RTF: about 9.13 sec for single image scan; 10 x 15 cm (4 x 6 in) color photo to e-mail (150 dpi, 24-bit): about 10.65 sec for single image scan; A4 (8.5 x 11 in) PDF to e-mail (300 dpi, 24-bit): about 12.98 sec for single image scan
Processor speed	120 Mhz
Memory Suppotrs	120 Mhz
Memory Suppotrs	64 MB
Ports	1 X USB 2.0
Control Panel	Scan button, Power button with a LED and a LED for Error indication
Power supplies	External Power Adapter Input Voltage range: 90 - 264 VAC , Rated Frequency: 50 - 60HZ, Worldwide use
Power consumption	3.6 Watts (ready), 1.0 Watts (sleep), 0.1 Watts (auto-off), 0.1 Watts (off)
Supported Temperature	Operating 10 to 35°C   Storage -40 to 60°C   humidity 15 to 80% RH (non-condensing)  Non-Operating Humidity 0 to 90% RH (non-condensing)
Compatible Operating Systems	OS X Mavericks 10.9, OS X Yosemite 10.10, OS X El Capitan 10.11, Microsoft Windows 10, 8.1, 8, 7: 32-bit or 64-bit
System requirement	Apple OS X Yosemite, OS X Mavericks, OS X Mountain Lion; 1 GB HD; Internet required; USB; Microsoft Windows 10, 8.1, 8, 7: 32-bit or 64-bit, 2 GB available hard disk space, CD-ROM/DVD drive or Internet connection, USB port, Microsoft Internet Explorer
System requirement	For Macintosh Apple OS X Yosemite, OS X Mavericks, OS X Mountain Lion; 1 GB HD; Internet required; USB

Environmental	RoHS-compliant
ENERGY STAR certified	Yes
Weight	2.6 kg
Dimensions	Without Stand 300 x 172.9 x 152.1 mm (W*D*H)
In The Box	HP ScanJet Pro 2000 s1 Sheet-feed Scanner; Install guide; Support flyers; Warranty cards; 2 CDs; Power cords; Power adaptor; USB cables (All regions)
Software included	Win: HP WIA scan driver, HP TWAIN scan driver, HP Scan, HP Scanner Tools Utility, Nuance PaperPort (Win only), I.R.I.S Readiris, I.R.I.S Cardiris (Win only), EMC ISIS (Win only)