



TP-Link Single-Mode Media Converter

Product Specification

Brand	TP-Link
Model	MC110CS
ports	100M dual SC/UPC port , 10/100M RJ45 port
Wave Length	1310nm
Standards	IEEE 802.3 IEEE 802.3u IEEE 802.3x
Basic Function	Half/Full-Duplex transfer mode for FX port Full Duplex Flow Control (IEEE 802.3x) Half Duplex Flow Control (Backpressure) Extends fiber distance up to 20km (12.4 miles)
Ports	1 100M dual SC/UPC port 1 10/100M RJ45 port (Auto MDI/MDIX)
Network Media 10BASE-T	UTP category 3, 4, 5 cable (maximum 100m) EIA/TIA-568 100Ω STP (maximum 100m)
Network Media 100BASE-T	UTP category 5, 5e cable (maximum 100m) EIA/TIA-568 100Ω STP (maximum 100m)
Network Media 100BASE-FX	Single-mode Fiber
LED Indicators	PWR, Link/Act
Power Consumption	2.4W
Operating Temperature	0°C~40°C (32°F~104°F)

Storage Temperature	-40°C~70°C (-40°F~158°F)
Operating Humidity	10%~90% non-condensing
Storage Humidity	5%~90% non-condensing